

10-17-00

A

10/16/00

10/16/00

Please type a plus sign (+) inside this box ☒

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PTO/SB/05 (08-00)

Approved for use through 10/31/2002. OMB 0851-0032

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

UTILITY PATENT APPLICATION TRANSMITTAL

Attorney Docket No. Garay 4-1-10(8018-21)

First Inventor J. Garay

Title METHOD FOR PROVIDING LONG-LIVED...

Express Mail Label No. EL599449462US

(Only for new nonprovisional applications under 37 CFR 1.53(b))

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

- ☒ Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original and a duplicate for fee processing)
- ☐ Applicant claims small entity status.
See 37 CFR 1.27.
- ☒ Specification [Total Pages 38]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or a computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure
- ☒ Drawing(s) (35 U.S.C. 113) [Total Sheets 4]
5. Oath or Declaration [Total Pages 5]
 - ☒ Newly executed (original or copy)
Copy from a prior application (37 CFR 1.63 (d))
 - ☐ (for continuation/divisional with Box 17 completed)
 - ☐ **DELETION OF INVENTOR(S)**
Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b).
- ☐ Application Data Sheet. See 37 CFR 1.76

ADDRESS TO:

Assistant Commissioner for Patents
Box Patent Application
Washington, DC 20231

- ☐ CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)
- Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 - ☐ Computer Readable Form (CRF)
 - Specification Sequence Listing on:
 - ☐ CD-ROM or CD-R (2 copies); or
 - ☐ paper
 - ☐ Statements verifying identity of above copies

ACCOMPANYING APPLICATION PARTS

- ☒ Assignment Papers (cover sheet & document(s))
- ☐ 37 CFR 3.73(b) Statement (when there is an assignee) ☒ Power of Attorney
- ☐ English Translation Document (if applicable)
- ☐ Information Disclosure Statement (IDS)/PTO-1449 ☐ Copies of IDS Citations
- ☐ Preliminary Amendment
- ☒ Return Receipt Postcard (MPEP 503) (Should be specifically itemized)
- ☐ Certified Copy of Priority Document(s) (if foreign priority is claimed)
- ☐ Other:

17. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76:

☐ Continuation ☐ Divisional ☐ Continuation-in-part (CIP) of prior application No. _____/_____

Prior application information.

Examiner _____

Group / Art Unit. _____

For CONTINUATION OR DIVISIONAL APPS only: The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

18. CORRESPONDENCE ADDRESS

☐ Customer Number or Bar Code Label



or ☐ Correspondence address below

Name

Frank Chau, Esq.

Address

F. CHAU & ASSOCIATES, LLP

1900 Hempstead Turnpike, Suite 501

City

East Meadow

State

New York

Zip Code

11554

Country

USA

Telephone

516-357-0091

Fax

516-357-0092

Name (Print/Type)

Frank Chau

Registration No. (Attorney/Agent)

34,136

Signature

Date 10/16/00

Burden Hour Statement: This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Box Patent Application, Washington, DC 20231.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2001

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT

(\$ 884.00)

Complete if Known

Application Number	
Filing Date	October 16, 2000
First Named Inventor	J. Garay
Examiner Name	
Group Art Unit	
Attorney Docket No.	Garay 4-1-10(8018-21)

METHOD OF PAYMENT

1. ☒ The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to:

Deposit
Account
Number

12-2325

Deposit
Account
Name

Lucent Technologies

- ☒ Charge Any Additional Fee Required
Under 37 CFR 1.16 and 1.17

- ☐ Applicant claims small entity status
See 37 CFR 1.27

2. ☐ Payment Enclosed:

☐ Check ☐ Credit card ☐ Money Order ☐ Other

FEE CALCULATION

1. BASIC FILING FEE

Large Entity Small Entity

Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
101	710	201	355	Utility filing fee	710
106	320	206	160	Design filing fee	
107	490	207	245	Plant filing fee	
108	710	208	355	Reissue filing fee	
114	150	214	75	Provisional filing fee	

SUBTOTAL (1) (\$ 710.00)

2. EXTRA CLAIM FEES

Total Claims	Extra Claims	Fee from below	Fee Paid
23	-20** = 3	18	54
4	-3** = 1	80	80
		270	

Large Entity Small Entity

Fee Code	Fee (\$)	Fee Code	Fee (\$)	Fee Description	Fee Paid
103	18	203	9	Claims in excess of 20	
102	80	202	40	Independent claims in excess of 3	
104	270	204	135	Multiple dependent claim, if not paid	
109	80	209	40	** Reissue independent claims over original patent	
110	18	210	9	** Reissue claims in excess of 20 and over original patent	

SUBTOTAL (2) (\$ 134.00)

**or number previously paid, if greater; For Reissues, see above

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity Fee Code	Small Entity Fee Code	Fee Description	Fee Paid		
105	130	205	65	Surcharge - late filing fee or oath	
127	50	227	25	Surcharge - late provisional filing fee or cover sheet	
139	130	139	130	Non-English specification	
147	2,520	147	2,520	For filing a request for <i>ex parte</i> reexamination	
112	920*	112	920*	Requesting publication of SIR prior to Examiner action	
113	1,840*	113	1,840*	Requesting publication of SIR after Examiner action	
115	110	215	55	Extension for reply within first month	
116	390	216	195	Extension for reply within second month	
117	890	217	445	Extension for reply within third month	
118	1,390	218	695	Extension for reply within fourth month	
128	1,890	228	945	Extension for reply within fifth month	
119	310	219	155	Notice of Appeal	
120	310	220	155	Filing a brief in support of an appeal	
121	270	221	135	Request for oral hearing	
138	1,510	138	1,510	Petition to institute a public use proceeding	
140	110	240	55	Petition to revive - unavoidable	
141	1,240	241	620	Petition to revive - unintentional	
142	1,240	242	620	Utility issue fee (or reissue)	
143	440	243	220	Design issue fee	
144	600	244	300	Plant issue fee	
122	130	122	130	Petitions to the Commissioner	
123	50	123	50	Petitions related to provisional applications	
126	240	126	240	Submission of Information Disclosure Stmt	
581	40	581	40	Recording each patent assignment per property (times number of properties)	40
146	710	246	355	Filing a submission after final rejection (37 CFR § 1.129(a))	
149	710	249	355	For each additional invention to be examined (37 CFR § 1.129(b))	
179	710	279	355	Request for Continued Examination (RCE)	
169	900	169	900	Request for expedited examination of a design application	

Other fee (specify) _____

*Reduced by Basic Filing Fee Paid

SUBTOTAL (3) (\$ 40.00)

SUBMITTED BY

Name (Print/Type) Frank Chau

Registration No.
(Attorney/Agent)

34,136

Complete (if applicable)

Telephone

516-357-0091

Signature

Date

10/16/00

WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.

Burden Hour Statement. This form is estimated to take 0.2 hours to complete. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, Washington, DC 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Assistant Commissioner for Patents, Washington, DC 20231.

IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

PATENT APPLICATION

Juan A. Garay, Jessica N. Staddon, Avishai Wool

CASE: Garay 4-1-10 (8018-21)

TITLE: METHOD FOR PROVIDING LONG-LIVED BROADCAST ENCRYPTION

BOX PATENT APPLICATION
ASSISTANT COMMISSIONER FOR PATENTS
WASHINGTON, D.C. 20231

SIR:

Enclosed are the following papers relating to the above-named application for patent:

38 sheets Specification, Claims and Abstract
4 sheets of Informal drawings
5 sheets Assignment with Cover Sheet
5 sheets Declaration and Power of Attorney

CLAIMS AS FILED				
	NO. FILED	NO. EXTRA	RATE	CALCULATIONS
Total Claims	23 - 20 =	3	x 18 =	\$ 54.00
Independent Claims	4 - 3 =	1	x 80 =	\$ 80.00
Multiple Dependent			x 260 =	\$
Basic Fee				\$ 710.00
			Total Fee:	\$ 844.00

Please file the application and charge **Lucent Technologies Deposit Account No. 12-2325** the amount of \$844.00, to cover the filing fee. **Duplicate copies of this letter are enclosed.** In the event of non-payment or improper payment of a required fee, the Commissioner is authorized to charge or to credit **Deposit Account No. 12-2325** as required to correct the error.

Please address all correspondence to **Frank Chau, F. Chau & Associates, LLP, 1900 Hempstead Turnpike, Suite 501, East Meadow, New York 11554.** However, telephone calls should be made to me at (516) 357-0091.

Respectfully,



Frank Chau
Reg. No. 34,136
Attorney for Applicant(s)

Date: October 16, 2000
Lucent Technologies, Inc.
600 Mountain Avenue
P.O. Box 636
Murray Hill, New Jersey 07974-0636

CERTIFICATION UNDER 37 C.F.R. § 1.10

I hereby certify that this Application transmittal and the documents referred to as enclosed are being deposited with the United States Postal Service on this date October 16, 2000 in an envelope as "Express Mail Post Office to Addressee" Mailing Label Number EL599449462US addressed to: Assistant Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.



Frank Chau



003101" 06482960

METHOD FOR PROVIDING LONG-LIVED BROADCAST ENCRYPTION

BACKGROUND

5 1. Technical Field:

The present application relates generally to broadcast encryption and, more particularly, to a long-lived broadcast encryption scheme that adapts to the presence of pirate decoders and maintains the security of broadcast to authorized users as encryption keys are compromised over time.

10 2. Description of Related Art:

In general, broadcast encryption (BE) techniques are employed to encrypt digital content to ensure that only privileged users are able to recover the content from an encrypted broadcast. Keys are allocated in such a way that users may be prevented on a short-term basis from recovering the message from the encrypted content. This short-
15 term exclusion of users occurs, for example, when a proper subset of users request to view a movie. The long-term exclusion (or, revocation) of a user is necessary when a user leaves the system entirely.

In practice, broadcast encryption schemes are typically smartcard-based, wherein key material is held in a "tamper-resistant", replaceable smartcard. These smartcards,
20 however, may be used to construct pirate smartcards (or pirate decoders) that allow non-paying customers to recover content. For instance, a coalition of unscrupulous users may conspire to attack a BE system by breaking open their smartcards to extract the keys and build pirate decoders using the extracted decryption keys, allowing non-authorized,

nonpaying users to utilize the pirate decoders to recover the content of encrypted broadcasts.

There are various conventional methods that have been employed to guard against the use of such pirate decoders. For instance, a broadcast encryption scheme may be coupled with a traceability (or traitor tracing) scheme to offer some protection against piracy. The traceability scheme is employed to render the practice of building pirate smartcards risky. This is accomplished by allocating keys to users in such a way that, once such a pirate smartcard is confiscated, at least one of the cards that was used to construct it can be identified.

There are disadvantages associated with such conventional schemes. For instance, traitor tracing schemes are typically designed having χ -traceability, wherein it is possible to identify at least one of the smartcards used to construct a given pirate card only if χ smartcards, at most, are used to construct the pirate card. Therefore, the security achieved in traceability schemes is limited by the necessity to have a bound on the number of users in a coalition. Another disadvantage associated with traceability schemes, as well as other conventional broadcast encryption schemes, is that they do not take into account the effect of the compromised keys when encrypting the content. Indeed, conventional broadcast encryption schemes do not provide a mechanism for providing continued, secured broadcasting to privileged sets of users after compromised keys that are contained on pirate decoders and/or smartcards of revoked users (whose contract has expired) have been identified. Instead, some schemes require that a private communication be made to each of the remaining users (e.g., over a network) when a single user is revoked in order to maintain the ability to revoke (or exclude) a certain

amount of users. In a BE scheme employing smartcards, however, the cost of reprogramming or replacing a large number of cards each time a user is revoked or a pirate smartcard is identified is extremely costly.

Accordingly, a broadcast encryption scheme that is not dependent on the size of the coalition constructing a pirate decoder and that retains an ability to broadcast securely in the presence of pirate smartcards, and consequently, compromised keys, is highly desirable.

SUMMARY OF THE INVENTION

The present invention is directed to a long-lived broadcast encryption method that adapts to the presence of compromised keys and continues to broadcast securely to privileged sets of users over time. In one aspect of the invention, a method for providing long-lived broadcast encryption comprises the steps of: allocating, to each of a plurality of subscribers, a corresponding set of subscriber keys; broadcasting encrypted content to the plurality of subscribers using a set of broadcast keys, wherein the encrypted content is decoded by a given subscriber using the subscriber's corresponding set of subscriber keys; modifying the set of broadcast keys, which are used for broadcasting encrypted content, by excluding compromised subscriber keys; and updating a set of subscriber keys corresponding to at least one subscriber when the at least one subscriber's set of subscriber keys comprises an amount of active keys that falls below a first predetermined threshold.

In another aspect of the invention, the set of subscriber keys allocated to a given user is encoded on a smartcard which is issued to the subscriber. When a pirate decoder is discovered, it is analyzed and the keys it contains are identified. Such keys are called

“compromised,” and are not used henceforth for broadcasting. Similarly, when a subscriber’s contract expires, the subscriber is “excluded,” and each of the keys contained on the excluded subscriber’s smartcard are considered compromised. The compromised keys are excluded from the broadcast encryption process. Over the course of time, while

5 compromised smartcards are identified, a state may exist in which the number of compromised smartcards (and consequently, the number of compromised keys) reaches a threshold above which secure communication to authorized users is not possible (because the number of active keys on their smartcards fall below a predefined threshold amount). To restore secure broadcast capabilities to such users, their smartcards are replaced with a

10 new smartcard comprising a new set of keys.

In yet another aspect of the invention, a long-live broadcast encryption scheme is reactive, being driven by the card compromises: either due to pirate decoders or the expiration of users’ contracts. These card compromises are used to divide time into administrative “epochs” comprising d compromises each. At the end of an epoch, the

15 service provider determines which authorized subscribers require card replacement, and such cards are replaced. Therefore, the primary cost in a long-lived BE scheme according to the present invention is the amount of recarding that is required in each epoch.

In another aspect of the present invention, a long-lived broadcast encryption

20 scheme employs an efficient (short term) randomized broadcast encryption scheme that yields an (m, α) - cover-free family to ensures with high probability that any coalition m smartcards can not cover a fraction α , of the keys contained on another smartcard. A $(\alpha r, |S_P|)$ - threshold protocol is used to broadcast to a privileged set P (authorized

subscribers) using a set of keys S_P , such that a fraction α of a total number of keys r contained on the smartcard of an authorized user is needed to recover the encrypted broadcast content. To render a compromised card useless as a decoder, all the keys contained on the compromised card are excluded from S_P , creating a new set S_P^1 .

- 5 Thereafter, broadcasting to the privileged set P is performed with an $(\alpha r, |S_P^1|)$ - threshold protocol. A recarding session is entered whenever d cards become unavailable. In a recarding session, new values are chosen randomly for all compromised keys, and then any user with less than αr active keys receives a new card. The parameter d in the fixed schedule will be based on the number of compromised users and the desired
- 10 transmission length.

In yet another aspect of the invention, one or more parameters of a long-lived broadcast encryption scheme can be selected, a priori, to ensure that only a bounded number of users need recarding in each epoch

- These and other aspects, features, and advantages of the present invention will
- 15 become apparent from the following detailed description of the preferred embodiments, which is to be read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

- Fig. 1 is a block diagram of a long-lived broadcast encryption system according to
- 20 an embodiment of the present invention;

Fig. 2 is a flow diagram of a method for providing long-lived broadcast encryption according to one aspect of the present invention;

Fig. 3 is a diagram illustrating different periods (epochs) of a randomized broadcast encryption scheme according to one aspect of the present invention;

Fig. 4 is a graphical diagram illustrating experimental results of smartcard replacement based on different values of the total number of keys in a long-lived broadcast encryption scheme according to one aspect of the present invention;

Fig. 5 is a graphical diagram illustrating experimental results of smartcard replacement based on different values of the number of keys per smartcard in a long-lived broadcast encryption scheme according to one aspect of the present invention; and

Fig. 6 is a graphical diagram illustrating experimental results of smartcard replacement based on different values of epoch length in a long-lived broadcast encryption scheme according to one aspect of the present invention.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

It is to be understood that the system modules and method steps described herein may be implemented in various forms of hardware, software, firmware, special purpose processors, or a combination thereof. In particular, the present invention is preferably implemented as an application comprising program instructions that are tangibly embodied on a program storage device (e.g., magnetic floppy disk, RAM, ROM, etc.) and executable by any device or machine comprising suitable architecture. It is to be further understood that, because some of the constituent system modules and process steps depicted in the accompanying Figures are preferably implemented in software, the actual connections between such components may differ depending upon the manner in which the present invention is programmed. Given the teachings herein, one of ordinary skill in

the related art will be able to contemplate these and similar implementations or configurations of the present invention.

Referring now to Fig. 1, a block diagram illustrates a system for providing long-lived BE (broadcast encryption) according to an embodiment of the present invention. In general, a long-lived BE system provides a mechanism for adapting a broadcast encryption scheme to the presence of compromised broadcast encryption keys that are contained on compromised (pirate) smartcards and smartcards of a subscribing user whose membership has expired or has been terminated ("excluded user"). The exemplary system 10 of Fig. 1 comprises a trusted server 11 associated with a service provider of certain broadcast content 12. In general, the trusted server 11 maintains security by authenticating and authorizing subscribers, and transmits encrypted broadcasts to privileged users (authorized subscribers) over a network 13 (e.g., LAN, WAN, Internet, etc). In a preferred embodiment, the service provider issues each subscriber a smartcard $S_1 \dots S_n$ comprising a set of decryption keys that are used for decoding encrypted broadcasts transmitted from the content provider (e.g., inserting the smartcard in a reader of a set-top box to decrypt a broadcasted event).

In the following discussion, the set of all subscribers/users (privileged and non-privileged/excluded) is denoted $\{u_1, \dots, u_n\}$, for $i = 1 \dots n$ where subscript n represents a total amount of users. The set of keys associated with the i^{th} user is denoted by U_i . Furthermore, a privileged sets of users, denoted P , is of a fixed size $n - m$, where n represents the set of all users (as indicated above) and m represents a number of users that are non-privileged/excluded (a set of m excluded/non-privileged users is denoted as X).

The trusted server 11 comprises a broadcast encryption module 14 and a key
 manager/generator module 15, which together, provide a mechanism for long-lived BE
 according to the present invention. In general, the broadcast encryption module 14
 employs a broadcast encryption technique based on symmetric key (or private key)
 5 encryption, and a broadcasting protocol for securely distributing broadcast content to a
 set of privileged users. More specifically, in a preferred embodiment, the broadcast
 encryption module 14 employs (1) an efficient (short-term) BE scheme (such as a
 randomized BE scheme described below) that yields an (m, α) -cover free family, and a
 unicast key between each user and the center; and (2) an $(s, |S_P|)$ - threshold protocol to
 10 broadcast to a privileged set of users $P = \{u_i \dots u_{n-m}\}$, where S_P denotes a set of keys used
 to broadcast to the privileged set P . If some user is unreachable under the $(s, |S_P|)$ -
 threshold protocol (i.e., as explained below, if too many of the user's keys appear on
 "dead" cards), then the unicast key will be used to reach that user. It is to be understood
 that a long-lived BE scheme according to a preferred embodiment of the present
 15 invention is an extension of the randomized BE scheme described, for example, in
 "Long-Lived Broadcast Encryption," by J. Garay, et al., Advances in Cryptology -
 Crypto '00, Lecture Notes in Computer Science 1880 (2000), pp. 333-352. It is to be
 understood, however, that (as discussed below) other BE schemes may be employed
 herein, preferably, BE schemes that are based on cover-free families (cover-free families
 20 are described in "Families of Finite Sets in Which No Set is Covered by the Union of r
 Others," by P. Erdos, et al., Israel Journal of Mathematics 51 (1985), pp. 75-89) . BE
 schemes based on such families are described, for example in "Efficient Methods for
 Integrating Broadcast Encryption and Traceability" by E Gafni, et al., Advances in

Cryptology - Crypto '99, Lecture Notes in Computer Science 1666 (1999), pp. 372-387

and “Coding Constructions for Blacklisting Problems without Computational

Assumptions,” by R. Kumar, et al., Advances in Cryptology - Crypto '99, Lecture Notes

in Computer Science 1666 (1999), pp. 609-623. In particular, BE schemes that are

5 tight with the proven lower bounds on the total number of keys in such schemes are preferably employed herein.

In the preferred embodiment employing a simple randomized BE scheme, the key generator/manager module 15 generates, manages and continuously updates a universal set of broadcast encryption keys \mathbf{K} that are stored in database 16. For purposes of the

10 following discussion, the universe of keys \mathbf{K} (at any given time) in database 16 is denoted by $\mathbf{K} = \{k_1, \dots, k_K\}$, where subscript K denotes a total amount of keys in database 16. In the preferred embodiment, the set of keys \mathbf{K} in database 16 comprises a plurality of key subsets $U_1 \dots U_i$, wherein each key subset U_i is allocated to a corresponding one of the n subscribers $u_1 \dots u_n$. Each key subset U_i in database 16 comprises r keys that are

15 randomly selected from the set of keys \mathbf{K} and allocated to a given subscriber, i.e., $(\forall i, |U_i| = r)$. The subset of keys associated with each subscriber is contained in a respective smartcard $S_1 \dots S_n$ which is issued to the subscriber by the service provider.

Furthermore, in the preferred embodiment employing a randomized BE scheme, the value of K is selected to ensure an (m, α) -cover free family with high probability.

20 More specifically, given the set of keys \mathbf{K} comprising a set of key subsets $U = \{U_1, \dots, U_n\}$, the set of key subsets comprises an (m, α) - cover-free family, if for all $i = 1, \dots, n$, and for all sets of m indices, $\{j_1, \dots, j_m\}$ not containing i , $|U_i \cap (\bigcup_{s=1}^m U_{j_s})| \leq (1 - \alpha)|U_i|$.

A cover free family guarantees that it is impossible for any coalition of m cards to cover

an α -fraction of key contained on another smartcard. As described in greater detail below, the lower bound on the total number of active keys K (that are stored in database 16) to ensure an (m, α) -cover free family with high probability (at least $1-\epsilon$, where ϵ is

any positive fraction) is $\Omega\left(\frac{n^{(m+1)/(r(1-\alpha)+1)}}{\epsilon}\right)$. A detailed proof for this lower

5 bound value for K is provided below.

It is to be understood that the factor of $n^{(m+1)/(r(1-\alpha)+1)}$ in the bound on K is due to the *cover-free* requirement, that with very high probability it is impossible for m smartcards to cover another smartcard (although the construction itself remains viable for any value of K). Consequently, the BE scheme may require a very large key set K ,
 10 where the total number of keys K is $\Omega(n^{m/r})$, when $r \geq m$, and $\Omega(n)$, otherwise (see, E. Gafni, et al., "Efficient Methods for Integrating Broadcast Encryption and Traceability," Advances in Cryptology - Crypto '99, Lecture Notes in Computer Science 1666 (1999), pp. 372-387). Indeed, these bounds may well be prohibitive for large user populations.

It is to be appreciated, however, that a long-lived BE scheme according to the
 15 present invention remains viable for values of K that fall below the lower bound value. In other words, the *cover-free* requirement is not necessary for implementing a long-lived BE scheme according to the present invention. Indeed, a *cover-free* scheme gives no guarantee on the system's behavior after $m+1$ cards are compromised. In addition, if a randomized attack model is considered (in which pirates pry open randomly selected
 20 cards), it is demonstrated (below) that even in a system with significantly fewer keys than an *m-cover-free* system, a set of m compromised cards will cover another card only with negligible probability. Therefore, in the long-term analysis (and in the experimental

results) described below, it is to be appreciated that values of m are not defined and the *cover-free* requirement is not adhered to for such values. In other words, a long-lived BE scheme according to the present invention guarantees that a coalition of m cards chosen uniformly at random does not cover any other card (with very high probability) using
5 substantially fewer keys as required by a *cover-free* scheme.

Referring again to Fig. 1, to broadcast encrypted content, the broadcast encryption module 14 preferably employs a broadcasting protocol based on a secret sharing scheme that allows a privileged set of users P to decrypt an encrypted broadcast transmitted from the service provider using the keys contained on their smartcards. In a preferred
10 embodiment, as indicated above, the broadcasting protocol is an $(s, |S_P|)$ - *threshold protocol* which is used to broadcast a message M to a privileged set of users $P = \{u_i \dots u_{n-m}\}$, where S_P denotes a set of keys used to broadcast to the privileged set P , and where s ($s \leq r$) denotes the number of keys out of the set U_i of r keys that a user needs to decode encrypted broadcast content. More specifically, with an $(s, |S_P|)$ -
15 threshold protocol being used to broadcast to privileged users P , K shares of M ($M_{k1}, M_{k2}, \dots, M_{kK}$) are created in such a manner that any s of the shares suffices to recover M . The shares corresponding to key held by user in $X = \{u_{n-m+1}, \dots u_n\}$ are discarded, and each remaining share is encrypted with its corresponding key and these encrypted messages are broadcast to the universe of users. In a preferred embodiment, $s = 1$, which
20 broadcasting protocol is sometimes referred to as an *OR* protocol as is known in the art. A detailed discussion of threshold protocols can be found, for example, in the article by R. Kumar, et al, entitled: "Coding Constructions for Blacklisting Problems Without

Computational Assumptions,” Advances in Cryptology – Crypto ’99, Lecture Notes in Computer Science 1666 (1999), pp. 609-623 (hereinafter referred to as “Kumar et al.”).

Threshold protocols are preferably employed herein as a component of a long-lived BE scheme because of their simplicity and because they yield broadcast encryption schemes with maximal resilience. A scheme is said to be ***m* - resilient** if ***m*** excluded (i.e., not privileged) users cannot recover the content even by pooling their keys. A broadcast encryption scheme with $(s, |S_P|)$ - threshold protocols for every privileged set ***P***, is ***m*-resilient**. In addition, the threshold protocols can be efficiently implemented with an error-correcting codes technique as described in Kumar et al. This technique involves generating shares of the content with an error correcting code. Consequently, the shares are much smaller than with a typical threshold secret sharing scheme, which results in a much smaller overhead (see D. Stinson, “Cryptography: Theory and Practice,” CRC Press, 1995, for a detailed discussion on secret sharing).

Generally, the number of transmissions, ***t***, in a broadcast encryption scheme is the number of keys that are used when encrypting the content. In the preferred embodiment in which the broadcast encryption module 14 implements an $(s, |S_P|)$ - threshold protocol to broadcast to a privileged set ***P***, the number of transmissions is $|S_P| = t$.

When using threshold protocols for broadcasting, a user should have sufficiently many keys left after the keys of ***m*** other users are excluded to recover the content from the broadcast. Conventionally, this was achieved by allocating keys to users in such a way that the set system is a cover-free family. As indicated above, however, with the long-lived perspective, the cover-free requirement is not a necessary requirement for a long-lived BE scheme according to the present invention. A long-lived BE scheme

according to the present invention focuses on how the broadcast encryption scheme is affected by pirate smartcards, which are assumed to be smartcards containing at least r keys, and other unavailable cards (i.e., cards of excluded users). As indicated above, a card may be compromised either because of piracy or simple because a user ceases to be an active subscriber and leaves the system. In either case, the keys on the card become permanently "unavailable" for use as encryption keys. A compromised (pirate) card may be a clone of some user's card or may contain a set of r keys that does not exactly match any of the set of keys of the n users in the system.

Furthermore, it is important to note that a key becomes "unavailable" for encryption use for one of two reasons: (1) the key is on a card belonging to an excluded user; or (2) the key is on a pirate decoder. The keys contained on a compromised smartcard (i.e., a pirate card or the card of an excluded user) are deemed "dead" (the compromised card is also deemed "dead"). On the other hand, a key that is not contained on a compromised card or one of an excluded user is considered "active." A smartcard is considered "clean" if it contains only "active" keys. The number of "dead" cards (i.e., either due to piracy or exclusion) is denoted d . It is to be understood that the reason behind the unavailability of a key has an effect on the BE scheme. When a key is dead because it appears on a compromised card, the key is permanently unavailable; whereas if it simple appears on an excluded user's card, its unavailability may be short term as the excluded user may be a privileged user at a later time.

In general, a long-lived BE method according to one aspect of the present invention for securely broadcasting to privileged users as smartcards become compromised comprises two basic components: (1) adjusting the set S_P of keys that are

used to encrypt the broadcast (e.g., by excluding “dead” keys from the set S_P and generating new keys to replace the dead keys) and (2) re-issuing smartcards to users (as necessary) whenever the number of “dead” cards d reaches a predetermined threshold.

The long-lived BE method is reactive in the sense that actions are taken in response to the number of compromised smartcards (which, for example, might hamper the continuity of service for privileged users, or bring transmission costs to unacceptable levels). In the preferred embodiment, the expected number of “dead” cards that can be tolerated in the randomized recarding scheme before it is necessary to recard a user is at least

$$\left(\frac{K-r}{r}\right) \ln(1/\alpha), \text{ or approximately } \frac{K}{r} \text{ dead smartcards (a detailed proof of which is}$$

provided below).

In this regard, the long-lived BE scheme of the present invention is divided into “epochs,” where each *epoch* represents a period in which the number of d smartcards has exceeded the predetermined threshold. At the end of *epoch i*, $i = 1, 2, \dots$, a determination is made as to which smartcards, if any, need replacing, and new cards are issued to the

corresponding users. For the long-term analysis, a variable C_i^j denotes the set of smartcards in *epoch j* that were created in *epoch i* (note that $C_1^1 = \{U_1 \dots U_n\}$). The following table summarizes the notation used herein.

Table 1

<ul style="list-style-type: none"> • $\{u_1, \dots, u_n\}$ is the set of all users. • U_i is the set of keys held by u_i. • $K = \{k_1, \dots, k_K\}$ is the set of all keys. • S_P is the set of keys used to broadcast to privileged set P. • n is the total number of users. • K is the total number keys. • r the number of keys per user. • t is the number of transmissions. Note that $S_P \leq t$.

- m is the number of users who are excluded.
- d is the number of unavailable (dead) cards at a certain point in time.
- C_i^j is the set of cards in epoch j that were created in epoch i .

It is to be appreciated that as indicated above, instead of the preferred randomized BE scheme described herein, the present invention may employ any suitable conventional BE scheme, such as BE schemes based on a *cover-free* family. For instance, a

5 randomized bucket-based scheme (such as described in Kumar, et al.) or a deterministic BE scheme based on polynomials (such as described in Gafni, et al.) may be extended to a long-lived BE scheme according to the present invention. Both constructions yield (m, α) - cover-free families. In the short term analysis (considering the first epoch), all three schemes are similar in terms of efficiency. The three BE schemes have very

10 similar costs. Each yield (m, α) -cover-free families with high probability when the total number of keys is close to the optimal bound of $n^{m/r}$ keys (this bound is for $\alpha=1/r$; i.e., no m users cover all another user's keys). In addition, all three schemes can tolerate approximately $\frac{K}{r}$ dead cards before recarding is necessary. Since the schemes are so close in terms of efficiency and cost, the simple randomized BE scheme is preferably

15 employed as the basis of a long-lived BE scheme according to the present invention since it is the most simple, as it is entirely random, and it has the advantage over the bucket-based scheme of featuring r and m as independent parameters.

Consequently, the preferred long-lived BE scheme is an extension of the simple randomized BE scheme. As indicated above, the extension is reactive based on card

20 compromises and recarding is performed once every d dead cards. For simplicity, the $(m, 1/r)$ -cover-free family version of the scheme (OR protocols). We emphasize that this

analysis is best applied to a stable privileged set of users, or to the entire set of users when m is small. In either case we expect to only have to recard a user when too many of their keys appear on compromised (i.e., permanently unavailable) cards.

The main cost associated with long-lived schemes is the number of cards that must be replaced. As demonstrated below, in the preferred long-live BE scheme, given a positive fraction β (and n , d , and r), at most βn of the cards need to be replaced during any recarding session, provided K and the number of sessions is sufficiently large. This is shown below by the experimental results.

Referring now to Fig. 2, a flow diagram illustrates long-lived BE method according to one aspect of the present invention. As indicated above, the long-lived BE method is preferably an extension of an efficient randomized BE method. Initially, each subscriber u_i of the broadcast service is allocated a set of decryption keys U_i (step 20). More specifically, in accordance with the underlying randomized BE scheme, each set of keys U_i is generated by randomly selecting r keys out of a set K comprising K keys. As indicated above, the value K may be selected to ensure that an (m, α) -cover free family is obtained having high probability (where, preferably, $\alpha = 1/r$, i.e., no m users cover all of another user's keys). It is to be noted that $\frac{1}{r} \leq \alpha \leq 1$. In a preferred embodiment, the set of keys U_i are encoded on smartcards, which are then issued to the respective subscribers.

Next, a set of keys S_P are selected (from the set of keys K) to broadcast to a privileged set of users P (step 21). As indicated above, a preferred broadcasting protocol is an $(ar, |S_P|)$ -threshold protocol, wherein a share is created for each key in the set S_P according to a $(ar, |S_P|)$ -threshold secret sharing scheme ($s = ar = 1$ denotes the number of

keys out of r that are needed to decode the content) and each share is encrypted with its corresponding key. In a preferred embodiment, $s=1$.

Over the course of time, one or more of the decryption keys that have been issued to the subscribing users may become compromised. As indicated above, a key is deemed
5 compromised (dead) if it is contained on a pirate smartcard or a smartcard of a subscribing user whose contract with the service provider has expired or been terminated (i.e., an excluded user). In addition, each pirate smartcard or smartcard belonging to an excluded user is considered dead. Therefore, when a pirate smartcard is discovered, it is analyzed and all the keys it contains are identified and deemed dead. Likewise, every
10 key contained on an excluded user's smartcard are deemed dead.

Accordingly, over the course of time, as compromised smartcards (pirate smartcards or smartcards of excluded users) are identified (affirmative result in step 22), to render such compromised/excluded cards useless, every key contained on such cards are deemed dead and, consequently, excluded from the set of keys S_P which is used to
15 broadcast to privileged users (step 23), thereby creating a new set S_P^1 (an so on). Thereafter, broadcasting to privileged users is performed via a $(ar, |S_P^1|)$ -threshold protocol (and so on). The identified pirate smartcards and smartcards belonging to an excluded user are deemed "dead" or "unavailable."

After compromised smartcards have been identified and deemed "dead", a
20 determination is made as to whether the amount of "dead" smartcards d (at the given time) has met a predefined threshold (step 24). As indicated above, in a preferred embodiment, the expected number of dead cards d that can be tolerated before recarding

is needed is at least $(\frac{K-r}{r}) \ln(1/\alpha)$. If the number of dead cards d has not met the predefined threshold (negative determination in step 24), then the latest modified set of encryption keys (e.g., S_P^1) will be used to encrypt the content broadcast to privileged users (step 25). Thereafter, additional compromised smartcards may be identified over
5 the course of time, resulting in continued modification (i.e., exclusion of the compromised keys) of the current set of keys used to encrypt the broadcast content (steps 22 and 23 are repeated).

On the other hand, if it is determined that the amount of dead cards d has met the predefined threshold (affirmative determination in step 24), a recarding session is
10 performed. As indicated above, in a preferred embodiment, a recarding session is performed once for each "epoch", wherein each *epoch* is a time period when the number of dead cards d meets the predefined threshold. In a preferred embodiment, a recarding session comprises updating the set of keys K by generating new keys to replace the dead keys (step 26). More specifically, let Z be the set of dead keys (i.e., all the keys
15 contained on the identified pirate and excluded smartcards) and let $z = |Z|$; note that $z \leq dr$. The update step comprises discarding all the keys in Z , and generating z new keys so that the resulting number of keys in the universal key set K is again K in total. The new set of all keys becomes $K' = (K \setminus Z) \cup Z'$. In short, new keys are generated for all
20 dead keys, and active keys are unchanged. The total number of active keys (i.e., keys that need to be stored by the broadcasting center (in database 16)) is unaffected by the recarding procedure.

00000000-00000000

The next step in the preferred recarding session is to determine if any (current) subscribers have less than a predetermined number of active keys on their smartcards (step 27). More specifically, in the preferred embodiment, a determination will be made as to whether there are any users having a current smartcard that contains less than αr active keys (preferably, $s=\alpha r=1$ and, therefore no active keys). Each user having a smartcard with less than the predefined number of active keys (e.g., 0 active keys) will be recarded. Recarding comprises the steps of allocating a new set of r keys by randomly selecting such keys from the updated set \mathbf{K} of K keys (step 28) and encoding the new keys on a new smartcard, which is then mailed to the user.

As indicated above, a key is considered dead either because it belongs to an excluded user or is on a compromised card. In the former case, the key is unavailable on what may be a short term basis, as an excluded user may well be a privileged user at another time. Hence, it is to be appreciated that the long term analysis described herein is best applied to a stable privileged set \mathbf{P} , or to the whole set of users when the number of excluded users, m , is small. Given this, it is very likely that users will only be recarded when more than $(1 - \alpha)r$ of their keys are permanently unavailable (i.e., contained in compromised cards) rather than simply temporarily unavailable, due to the current set of excluded users. Indeed, the primary motivation for recarding users is the presence of compromised (pirate) cards.

It is to be appreciated that the recarding process (steps 26, 27 and 28) depicted in Fig. 2 is repeated for each epoch (i.e., for each affirmative result in step 24). As keys get compromised and smartcard are reissued to users, the users are partitioned into sets of users with cards with fresh keys, and users with cards containing keys some of which are

dead. This process is depicted in Figure 3. Recall that C_i^j represents the set of smartcards in *epoch j* that were created in *epoch i*. Initially in *epoch 1*,

$C_1^1 = \{U_1, \dots, U_n\}$. In a recarding session in epoch 2, selecting (randomly) d dead cards from C_1^1 yields C_2^2 , the set of users that need to be recarded, as well as $C_1^2 = C_1^1 \setminus C_2^2$; in

epoch 2, selecting d random cards from C_1^2 and C_2^2 yields C_3^3 as well as C_1^3 and C_2^3 ; and so on. As described in detail below, there comes a time in which steady state is reached where only a bounded number of users C_j^j need to be recarded in any epoch. A detailed proof of this steady state condition is provided below, along with an empirical analysis.

10 PROOFS

Lemma 1. As indicated above, the lower bound on the total number of active keys K (that are stored in database 16) in the randomized BE scheme to ensure an (m, α) -cover free family with high probability (at least $1-\epsilon$, where ϵ is any positive fraction) is

$\Omega\left(\frac{n^{(m+1)/(r(1-\alpha)+1)}}{\epsilon}\right)$. This lower bound value is derived as follows.

15 Consider $m+1$ users, u, u_1, u_2, \dots, u_m . First we bound the probability that u_1, \dots, u_m cover more than $(1-\alpha)r$ of u 's keys. Since $|\bigcup_{i=1}^m U_i| \leq mr$, we have the following bound:

$$\Pr(|U \cap (\bigcup_{i=1}^m U_i)| > (1-\alpha)r) \leq \frac{\binom{mr}{(1-\alpha)r+1} \binom{K-(1-\alpha)r-1}{ar-1} + \binom{mr}{(1-\alpha)r+2} \binom{K-(1-\alpha)r-2}{ar-2} + \dots + \binom{mr}{r}}{\binom{K}{r}}$$

20 Using binomial bounds and simplifying, we have:

bound can be made small through appropriate choices of K , r and d . This analysis comprises three components. First, given fixed valued of the parameters, there exists an integer ℓ_1 , such that the probability that a card is covered (and hence, needs to be refreshed) within ℓ_1 epochs, is negligible. The intuition for this result is that if a card has been refreshed recently, then it is unlikely that it will be covered again within a small number of epochs. This result indicates that the contribution to $E(|C_{i+1}^{i+1}|)$ from the first ℓ_1 terms of inequality 1 of *Lemma 3* above is fairly small. Secondly, the later terms in inequality 1 may also not contribute much to the upper bound on $E(|C_{i+1}^{i+1}|)$. In particular, there exists an integer, ℓ_2 , (greater than ℓ_1), such that it is unlikely that a card will not be covered within ℓ_2 epochs. Note that this implies that when $i - j \geq \ell_2$, $E(|C_j^i|)$ is fairly small, and hence, will not contribute much to the upper bounds on $E(|C_{i+1}^{i+1}|)$. Lastly, ℓ_1 and ℓ_2 are on the order of K/rd , hence the dominating terms are those for which $i-j$ is $\Theta(K/rd)$, and this leads to an approximation for the upper bound of the steady state recard rate, β . The following proof demonstrates this analysis in detail.

Lemma 4: Assume n , K , r , d and $\epsilon > 0$ are given, the following are true:

1. If $\ell_1 \in O\left(\frac{\epsilon^{1/r} K}{rd}\right)$, then the probability that a card is covered within ℓ_1

epochs is less than ϵ .

2. If $\ell_2 \in \Omega\left(\frac{(1-\varepsilon)^{1/r} K}{rd}\right)$, then the probability that a card survives for

more than ℓ_2 epochs before it is covered is less than ϵ .

3. If $i-j \in \Theta\left(\frac{K}{rd}\right)$, then the coefficient of $E(|C_j^i|)$ in inequality 1 of the

above Lemma 3 is approximately $\left(1 - \left(\frac{1 - r/K}{e^c}\right)^d\right)^r$, where c is a constant.

5 The proof is as follows:

1. The probability that a card is covered by $d\ell_1$ randomly chosen cards is

$\left(1 - \left(1 - \frac{r}{K}\right)^{d\ell_1}\right)^r$. Setting this quantity less than ϵ and solving for ℓ_1 yields

$$\ell_1 \succ \frac{\ln(1 - \varepsilon)^{1/r}}{d \ln(1 - r/K)}.$$

10 2. The probability that a card is not covered within ℓ_2 epochs is

$\left(1 - \left(1 - \frac{r}{K}\right)^{d\ell_2}\right)^r$. Setting this quantity less than ϵ and solving for ℓ_2 yields

$$\ell_2 \succ \left(\frac{K}{rd}(1 - \varepsilon)^{1/r}\right)$$

3. Assuming that $i - j = \frac{cK}{rd}$ for some constant c , we'll bound the

contribution of $i - j = \frac{cK}{rd}$ to the inequality in Lemma 3 (i.e., we'll bound the coefficient

of $E(|C_j^i|)$ - given the earlier results, this bound is an approximate upper bound to β , the long term steady state. When $i - j = \frac{cK}{rd}$, the coefficient of $E(|C_j^i|)$ is

$\left(1 - \left(1 - \frac{r}{K}\right)^d\right)^{\frac{cK}{rd} + 1}$. When K is sufficiently large, this is the order of

$$\left(1 - \frac{\left(1 - \frac{r}{K}\right)^d}{e^c}\right)^r.$$

- 5 When combined with parts 1 and 2, part 3 of this Lemma indicates that the steady state recard rate β should decrease with K (which agrees with the experimental results that follow). The quantity also increases with d , which agrees with the basic intuition that the longer we wait to recard, the more recarding we will have to do.

Experimental Results

- 10 The following experiments illustrate the dynamics of smartcard replacement in accordance with a long-lived BE scheme according to the present invention and corroborate the steady state claim. In these experiments, equation 1 of Lemma 3 was evaluated (assuming an equality rather than an inequality) for a variety of parameter settings to track the number of cards that were issued in every epoch. Furthermore, we
- 15 focused on the random attack model, and assumed that, in each epoch, the dead cards d are selected uniformly at random from the set of user cards. As indicated above, a long-lived BE scheme according to the present invention guarantees that a coalition of m cards chosen uniformly at random does not cover any other card (with very high probability) using substantially fewer keys. Thus, in the long-term analysis, and in the following
- 20 simulation, we did not adhere to the *cover-free* requirement and, consequently, the value

the steady state rate of card reissue is lower for larger K . For instance, steady state occurs at ≈ 9400 cards per *epoch* for $K=1000$, whereas steady state occurs at ≈ 2000 cards per *epoch* for $K=5000$. Overall, we see that increasing K improves all the aspects of the reissue strategy. Therefore, it is preferable to use the largest possible K that is within the technological requirements.

Next, Fig. 5 is a diagram that illustrates the effect of increasing the card capacity r . More specifically, Fig. 5 illustrates three curves representing the number of cards reissued per epoch, with $n=100,000$, $K=5000$ and $d=20$, for values of $r=30, 20$ and 10 . We can see that as the value of r increases, the cost of card reissue increases: the curves having larger values for r result in higher steady state reissue rates and higher peak reissue rates. This is consistent with the fact that as r increases, we expect each key to be contained in more cards, so the effect of a compromised key is more widespread. In addition, as indicated above, we expect to have to recard users sooner when r is large (and K is fixed). Having a smaller r , however, means that the expected transmission length would be longer; at the extreme, setting $r=1$ would give optimal reissue rates (no cards need to be reissued), with very long transmissions.

Next, Fig. 6 illustrates the effect of increasing the epoch length d . More specifically, Fig. 6 illustrates three curves representing the accumulated total number of reissued cards, with $n=100,000$, $K=5000$ and $r=10$, for epoch lengths $d=20, 40$ and 80 . Fig. 6 illustrates that a longer epoch length results in a smaller total number of reissued cards. On the other hand, as the length of the epoch increases, the number of compromised keys during each epoch increases, thereby possibly resulting in many users

not being broadcasted to securely (in the absence of unicasts). Consequently, the recarding costs and transmission costs may influence the choice of d .

In summary, a long-lived broadcast encryption method according to the present invention provides a mechanism for adapting broadcast encryption to the presence of pirate decoders and maintaining the security of broadcasts to privileged users while rendering all pirate decoders useless. A long-lived broadcast encryption scheme is a more comprehensive solution to piracy than conventional methods such as traitor tracing schemes, because the latter only seek to identify the makers of pirate decoders and do not provide a mechanism for maintaining secured broadcasts once keys have been compromised. Indeed, one fundamental difference between a long-lived BE scheme as described herein and conventional techniques is that the long-live BE scheme seeks to minimize the amount of communication (recarding) that is needed by adapting to the presence of compromised cards (or equivalently, revoked users) by removing the keys contained on a pirate decoder (or revoked user's cards) from the encryption process. Consequently, a long-lived BE scheme as described herein is a more efficient long-term solution than conventional revocation schemes because is minimized the amount of recarding that must be done in the long-term.

In addition, as described above, although a conventional broadcast encryption scheme may only be designed to allow any set of m users to be excluded, a long-lived BE scheme according to the present invention can tolerate a high number of compromised cards (in addition to the m excluded cards) before any users need to be recarded. Indeed, through an appropriate choice of parameters, the affected number of users (who need to be recarded in a given epoch during steady state) can be a small fraction of the total

number of users. That is, for a long-lived broadcast encryption scheme according to the present invention, for any positive fraction β , the parameter values may be selected, *a priori*, in such a way to ensure that eventually, at most β of the n cards must be replaced in each epoch.

- 5 Although illustrative embodiments have been described herein with reference to the accompanying drawings, it is to be understood that the present system and method is not limited to those precise embodiments, and that various other changes and modifications may be affected therein by one skilled in the art without departing from the scope and spirit of the invention. It is to be understood that all such changes and
- 10 modifications are intended to be included within the scope of the invention as defined by the appended claims.

009T01" 0848950
0963490-101600

WHAT IS CLAIMED IS:

1. A broadcast encryption method, comprising the steps of:
- allocating, to each of a plurality of subscribers, a corresponding set of subscriber keys;
- 5 broadcasting encrypted content to the plurality of subscribers using a set of broadcast keys, wherein the encrypted content is decoded by a given subscriber using the subscriber's corresponding set of subscriber keys;
- modifying the set of broadcast keys, which are used for broadcasting encrypted content, by excluding compromised subscriber keys; and
- 10 updating a set of subscriber keys corresponding to at least one subscriber when the at least one subscriber's set of subscriber keys comprises an amount of active keys that falls below a first predetermined threshold.
2. The method of claim 1, wherein each set of subscriber keys is encoded on a
- 15 smartcard that is issued to the corresponding subscriber.
3. The method of claim 2, further comprising the steps of:
- identifying a compromised smartcard; and
- identifying each subscriber key contained on the compromised smartcard as a
- 20 compromised key.
4. The method of claim 3, wherein a compromised smartcard comprises one of a pirate smartcard and a smartcard of an excluded subscriber.

5 5. The method of claim 4, wherein the step of updating comprises the steps of:
 tracking a total amount of compromised cards; and
 reissuing a smartcard comprising the updated set of subscriber keys when the total
 amount of compromised cards meets a second predefined threshold.

6. The method of claim 1, wherein the first predetermined threshold is one key.

10 7. A broadcast encryption method, comprising the steps of:
 allocating a set of subscriber keys to each of a plurality of n subscribers, wherein
 each set of subscriber keys is generated by randomly selecting r keys from a universal set
 comprising K keys;
 broadcasting encrypted content to the n subscribers using a set of broadcast keys
 S_p selected from the universal set of keys;
 identifying at least one compromised subscriber key;
 adjusting S_p by excluding the at least one compromised subscriber key; and
 updating a set of subscriber keys corresponding to at least one subscriber when
 the at least one subscriber's set of subscriber keys comprises an amount of active keys
 that falls below a first predetermined threshold.

20

8. The method of claim 7, wherein the step of allocating is performed using a
 randomized broadcast encryption scheme wherein K is selected to ensure an (m, α) cover
 free family with high probability that the sets of subscriber keys corresponding to a

coalition of m subscribers can not cover a fraction α of r keys comprising the set of subscriber keys of another subscriber.

9. The method of claim 8, wherein the step of broadcasting is performed using
5 an $(\alpha r, |S_p|)$ - threshold broadcast protocol.

10. The method of claim 9, wherein $\alpha r=1$

11. The method of claim 7, wherein each set of subscriber keys is encoded on a
10 separate smartcard that is issued to the corresponding subscriber.

12. The method of claim 11, wherein the step of identifying at least one
compromised subscriber key comprises the steps of:

identifying a compromised smartcard; and
15 identifying each subscriber key contained on the compromised card as a
compromised key.

13. The method of claim 12, wherein a compromised smartcard comprises one of
a pirate smartcard and a smartcard of an excluded subscriber.

20

14. The method of claim 12, wherein the step of updating comprises the steps of:
tracking a total amount of compromised smartcards; and

reissuing a smartcard comprising the updated set of subscriber keys when the total amount of compromised cards meets a second predefined threshold d .

15. The method of claim 14, wherein d is substantially equal to K/r .

5

16. The method of claim 14, wherein the step of reissuing comprises the steps of:
generating a new key for each compromised key to update the universal set of
keys; and

randomly selecting r keys from the updated universal set of keys to generate the
10 updated set of subscriber keys.

17. The method of claim 14, wherein K , r and d are selected to obtain a bound on the number of subscribers that are reissued smartcards in recarding sessions.

15 18. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for performing broadcast encryption, the method steps comprising:

allocating, to each of a plurality of subscribers, a corresponding set of subscriber
keys;

20 broadcasting encrypted content to the plurality of subscribers using a set of broadcast keys, wherein the encrypted content is decoded by a given subscriber using the subscriber's corresponding set of subscriber keys;

modifying the set of broadcast keys, which are used for broadcasting encrypted content, by excluding compromised subscriber keys; and

updating a set of subscriber keys corresponding to at least one subscriber when the at least one subscriber's set of subscriber keys comprises an amount of active keys
5 that falls below a first predetermined threshold.

19. The program storage device of claim 18, further comprising instructions for performing the step of:

identifying each subscriber key contained on a compromised smartcard as a
10 compromised key.

20. The program storage device of claim 19, wherein the instructions for performing the step of updating comprise instructions for performing the steps of:

tracking a total amount of compromised cards; and
15 encoding a smartcard with the updated set of subscriber keys when the total amount of compromised cards meets a second predefined threshold.

21. The program storage device of claim 18, wherein the first predetermined threshold comprises one key.

20

22. A program storage device readable by a machine, tangibly embodying a program of instructions executable by the machine to perform method steps for broadcast encryption, the method comprising the steps of:

allocating a set of subscriber keys to each of a plurality of n subscribers, wherein each set of subscriber keys is generated by randomly selecting r keys from a universal set comprising K keys;

broadcasting encrypted content to the n subscribers using a set of broadcast keys

5 S_p selected from the universal set of keys;

identifying at least one compromised subscriber key;


adjusting S_p by excluding the at least one compromised subscriber key; and

updating a set of subscriber keys corresponding to at least one subscriber when
the at least one subscriber's set of subscriber keys comprises an amount of active keys
10 that falls below a first predetermined threshold.

23. The program storage device of claim 22, wherein the instructions for performing the step of allocating comprise instructions for performing a randomized broadcast encryption scheme wherein K is selected to ensure an (m, α) cover free family
15 with high probability that the sets of subscriber keys corresponding to a coalition of m subscribers can not cover a fraction α of r keys comprising the set of subscriber keys of another subscriber.

ABSTRACT OF THE DISCLOSURE

A long-lived broadcast encryption method that adapts to the presence of compromised keys and continues to broadcast securely to privileged sets of users over time. In one aspect, a method for providing long-lived broadcast encryption comprises the steps of: allocating, to each of a plurality of subscribers, a corresponding set of subscriber keys; broadcasting encrypted content to the plurality of subscribers using a set of broadcast keys, wherein the encrypted content is decoded by a given subscriber using the subscriber's corresponding set of subscriber keys; modifying the set of broadcast keys, which are used for broadcasting encrypted content, by excluding compromised subscriber keys; and updating a set of subscriber keys corresponding to at least one subscriber when the at least one subscriber's set of subscriber keys comprises an amount of active keys that falls below a first predetermined threshold. In a long-lived broadcast encryption scheme, for any positive fraction β , a plurality of parameter values may be selected, *a priori*, in such a way to ensure that a steady state is achieved wherein, at most β of the total number of issued cards need to be replaced in a given recarding session.






FIG. 2

003707-0648960




Fig. 3




Fig. 4




Fig. 5




Fig. 6

IN THE UNITED STATES
PATENT AND TRADEMARK OFFICE

Declaration and Power of Attorney

As the below named inventor, I hereby declare that:

My residence, post office address and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor of the subject matter which is claimed and for which a patent is sought on the invention entitled **METHOD FOR PROVIDING LONG-LIVED BROADCAST ENCRYPTION** the specification of which is attached hereto.

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by an amendment, if any, specifically referred to in this oath or declaration.

I acknowledge the duty to disclose all information known to me which is material to patentability as defined in Title 37, Code of Federal Regulations, 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

None

I hereby claim the benefit under Title 35, United States Code, 120 of any United States application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, 112, I acknowledge the duty to disclose all information known to me to be material to patentability as defined in Title 37, Code of Federal Regulations, 1.56 which became available between the filing date of the prior application and the national or PCT international filing date of this application:

None

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

009490-10400

I hereby appoint the following attorney(s) with full power of substitution and revocation, to prosecute said application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith:

Lester H. Birnbaum	(Reg. No. 25830)
Richard J. Botos	(Reg. No. 32016)
Jeffery J. Brosemer	(Reg. No. 36096)
Kenneth M. Brown	(Reg. No. 37590)
Craig J. Cox	(Reg. No. 39643)
Donald P. Dinella	(Reg. No. 39961)
Guy Eriksen	(Reg. No. 41736)
Martin I. Finston	(Reg. No. 31613)
James H. Fox	(Reg. No. 29379)
William S. Francos	(Reg. No. 38456)
Barry H. Freedman	(Reg. No. 26166)
Julio A. Garceran	(Reg. No. 37138)
Mony R. Ghose	(Reg. No. 38159)
Jimmy Goo	(Reg. No. 36528)
Anthony Grillo	(Reg. No. 36535)
Stephen M. Gurey	(Reg. No. 27336)
John M. Harman	(Reg. No. 38173)
Michael B. Johannesen	(Reg. No. 35557)
Mark A. Kurisko	(Reg. No. 38944)
Irena Lager	(Reg. No. 39260)
Christopher N. Malvone	(Reg. No. 34866)
Scott W. McLellan	(Reg. No. 30776)
Martin G. Meder	(Reg. No. 34674)
John C. Moran	(Reg. No. 30782)
Michael A. Morra	(Reg. No. 28975)
Gregory J. Murgia	(Reg. No. 41209)
Claude R. Narcisse	(Reg. No. 38979)
Joseph J. Opalach	(Reg. No. 36229)
Neil R. Ormos	(Reg. No. 35309)
Eugen E. Pacher	(Reg. No. 29964)
Jack R. Penrod	(Reg. No. 31864)
Daniel J. Piotrowski	(Reg. No. 42079)
Gregory C. Ranieri	(Reg. No. 29695)
Scott J. Rittman	(Reg. No. 39010)
Eugene J. Rosenthal	(Reg. No. 36658)
Bruce S. Schneider	(Reg. No. 27949)
Ronald D. Slusky	(Reg. No. 26585)
David L. Smith	(Reg. No. 30592)


009T0T"06788960

Patricia A. Verlangieri	(Reg. No. 42201)
John P. Veschi	(Reg. No. 39058)
David Volejnicek	(Reg. No. 29355)
Charles L. Warren	(Reg. No. 27407)
Jeffrey M. Weinick	(Reg. No. 36304)
Eli Weiss	(Reg. No. 17765)

I hereby appoint the attorney(s) on ATTACHMENT A as associate attorney(s) in the aforementioned application, with full power solely to prosecute said application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected with the prosecution of said application. No other powers are granted to such associate attorney(s) and such associate attorney(s) are specifically denied any power of substitution or revocation.

Full name of sole inventor (or 1st joint inventor): **Juan A. Garay**

Inventor's
signature



Date 10/6/2000

Residence:

West New York, NJ

Citizenship:


Argentina

Post Office Address:

6040 Boulevard East - 16D
West New York, NJ 07093

Full name of 2nd joint inventor: **Jessica N. Staddon**

Inventor's
signature



Date 10/13/2000

Residence:

Redwood City, CA 94061

Citizenship:

USA

Post Office Address:

2325 Cheshire Way
Redwood City, CA 94061

009101-0648950

Case Name and No. Garay 4-1-10 (8018-21) 4

Full name of 3rd joint inventor: **Avishai Wool**

Inventor's
signature Avishai Wool Date Oct 6, 2000

Residence: Livingston, NJ

Citizenship: Israel

Post Office Address: 45 Fellswood Drive
Livingston, NJ 07039

0030T=042300

ATTACHMENT A

Attorney Name(s):	<u>Frank Chau</u>	Reg. No.:	<u>34,136</u>
	<u>James J. Bitetto</u>		<u>40,513</u>
	<u>Frank V. DeRosa</u>		<u>43,584</u>
	<u>Gaspere J. Randazzo</u>		<u>41,528</u>

Telephone calls should be made to **F. Chau & Associates, LLP** at:

Phone No.: (516) 357-0091

Fax No.: (516) 357-0092

All written communications are to be addressed to:

**Frank Chau
F. Chau & Associates, LLP
1900 Hempstead Turnpike, Suite 501
East Meadow, NY 11554**

009101" 06483350